

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	2,5 mm
Wear layer	EN ISO 24340	0,55 mm
Surface treatment		K-Guard+ PU coating
Guarantee <sup>1</sup>	Light industrial Commercial Residential	15 years 15 years 30 years
Bevelled edge		Micro
Mass per unit area	EN ISO 23997	4398 g/m <sup>2</sup>
Standards	EN 649/EN ISO 10582	Heterogeneous PVC
Classification	EN 685/EN ISO 10874 - Light industrial EN 685/EN ISO 10874 - Commercial EN 685/EN ISO 10874 - Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 660-2 EN ISO 10582	Group T Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0,25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL <sub>w</sub> = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0,1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0,0097 m <sup>2</sup> K/W Suitable for underfloor heating. Max 27°C
Slip resistance <sup>2</sup>	EN 13893 DIN 51130	DS R10
Adhesive	Universal Acrylic Epoxy High Temperature+ Pressure Sensitive	Yes Yes Yes Yes Yes
Environmental	French VOC regulation (ISO 16000) Indoor Air Comfort  Floorscore SCS-EC10.3-2014 v4.0  Environmental Product Declaration DIBt/AgBB	A+  Gold certification; Compliant low emitting VOC emissions.  Indoor air quality certified; Compliant low emitting VOC emissions.  External third-party verified Type III EPD Pass
Recycling		Suitable
Phthalate free		Yes

<sup>1</sup> Subject to terms see website.

<sup>2</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

**For more information:**

Designflooring = T: +44 (0) 1386 820 105 | F: +44 (0) 1386 820 132

Designflooring France = T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH = T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland = T: 020 200 8282 | F: 020 200 8386

Email: [info@designflooring.com](mailto:info@designflooring.com)

[www.designflooring.com](http://www.designflooring.com)

08/21



EN 14041:2004 (DOP 2017/OP/EN/02)
Notified body 0493 Floor coverings (internal)
ISO 10874 Class 23/33/42 Manufactured to ISO 10582



	Product Code	Size		Box Quantity		Slip Resistance DIN 51130
		mm	inches	m <sup>2</sup>	Pieces	
Wood Designs	WP311	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	WP312	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	WP313	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	WP316	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	WP318	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	WP327	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	WP329	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	WP330	914,4 x 152,4	36" x 6"	3,345	24 Planks	R10
	WP411	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP412	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP413	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP414	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP418	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP419	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP420	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP421	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP422	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
	WP423	1219,2 x 228,6	48" x 9"	3,345	12 Planks	R10
		REN113	914,4 x 101,6	36" x 4"	3,345	36 Planks
Stone Designs	SP212	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	SP213	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	SP214	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	SP215	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	SP216	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	SP217	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	SP218	457,2 x 609,6	18" x 24"	3,345	12 Tiles	R10
	SP711	457,2 x 914,4	18" x 36"	3,345	8 Tiles	R10
	SP713	457,2 x 914,4	18" x 36"	3,345	8 Tiles	R10
	SP714	457,2 x 914,4	18" x 36"	3,345	8 Tiles	R10
	SP716	457,2 x 914,4	18" x 36"	3,345	8 Tiles	R10